

CONTROL DE ACCESO IP

SERVIDOR WEB INTERNO

Controles de Acceso IP para 1, 2 y 4 puertas con web server interno para alta y baja de usuarios, configuración e informes, antipassback, entrada para lectores w26 bits std. Ideales para instalaciones pequeñas y medianas donde se requiera versatilidad, robustez y confiabilidad.



Model	PCT-201	PCT-202	PCT-204
Door Capacity	1	2	4
Wiegand Interface	2	4	4
Exit Button Connection	1	2	4
EM Lock Connection	1	2	4
Sensor Connection	1	2	4
Access Log	60,000 entries	60,000 entries	60,000 entries
Fire Alarm Connection	V	V	V
Power Box LED Connection	V	V	V
TCP/IP Interface	V	V	V
Two Ways Access Control	V	V	X
Accessibility To Wiegand Reader's Light and Buzzer	V	V	V
Power Requirement	DC 9~24V	DC 9~24V	DC 9~24V
Power Consumption (Exclude external device)	180mA	220mA	300mA
Suggest Power Spec. (Include wiegand readers)	1A	1.5A	2A
Wiegand Reader Power Requirement	9~24V	9~24V	9~24V
Reader Communication Mode	Wiegand 26~66 bit	Wiegand 26~66 bit	Wiegand 26~66 bit
Max. Range For Wiegand Reader	80 Meters	80 Meters	80 Meters
Operation Temperature	0~55 °C	0~55 °C	0~55 °C
Operation Humidity	5%~80%,RH	5%~80%,RH	5%~80%,RH
Dimension/Weight	138x114x27mm/150g	200x114x27mm/200g	200x114x27mm/250g